(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 30 October 2003 (30.10.2003)

PCT

(10) International Publication Number WO 03/089776 A1

- (51) International Patent Classification⁷: F02B 47/02
- F02M 25/028,
- (21) International Application Number: PCT/FI03/00302
- (22) International Filing Date: 16 April 2003 (16.04.2003)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 20020754


19 April 2002 (19.04.2002) FI

- (71) Applicant (for all designated States except US): MAR-IOFF CORPORATION OY [FI/FI]; P.O.BOX 25, Hakamäenkuja 4, FIN-01511 Vantaa (FI).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): SUNDHOLM, Göran [FI/FI]; Ilmari Kiannon kuja 3, FIN-04310 Tuusula (FI).

- (74) Agent: HEINÄNEN OY; Annankatu 31-33 C, FIN-00100 Helsinki (FI).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR THE CONTROL OF A SPRAYING APPARATUS



method (57) Abstract: Α controlling a spraying apparatus, especially a spraying apparatus designed for the humidification of intake air, said apparatus comprising at least two spraying nozzles (la, lb, lc, ld) for injecting liquid into the intake air. In accordance with the control system's instructions, when the required amount of liquid to be supplied through the nozzles increases, liquid flow passages are opened for more nozzles (1a, 1b, 1c, 1d) and/or the liquid flow is directed into a flow passage leading to a nozzle that permits a larger liquid flow through it per unit of time, and when the required amount of liquid to be supplied through the nozzles decreases, liquid flow channels are closed at least for some of the nozzles (la, lb, lc, ld) and/or the liquid flow is directed to a nozzle that permits a smaller liquid flow through it per unit of time.

EXPRESS MAIL LABEL NO.: EV 481671013 US



WO 03/089776 A1

49/511938 Rec'd PCR/PTO 19 OCT 2004

Declaration under Rule 4.17:

- of inventorship (Rule 4.17(iv)) for US only

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.